

**Method and apparatus for determining speech coding parameters**

**Patent number:** CN1132155C  
**Publication date:** 2002-02-20  
**Inventor:**  
**Applicant:**  
**Classification:**  
**- international:** G10L19/08  
**- european:**  
**Application number:** CN20000802640 20000104  
**Priority number(s):** FI19990000033 19990108

**Also published as:**

WO0041163 (A3)  
WO0041163 (A2)  
EP1145221 (A3)  
EP1145221 (A2)  
US6587817 (B1)  
FI990033 (A)  
FI114833B (B)


less &lt;&lt;

[Report a data error here](#)

Abstract not available for CN1132155C

Abstract of corresponding document: **US6587817**

A method which comprises forming a first noise reduction frame (18) containing speech samples; which is windowed by a first window function. For the windowed frame, noise reduction is performed for producing a second noise reduction frame (19; 45). A speech coding frame (44) to be formed comprises noise-reduced samples of at least two successive second noise reduction frames (45, 46), partly summed with one another. On the basis of said speech coding frame (44), a set of speech coding parameters  $p_j$  are determined. A lookahead part (42) of the speech coding frame is at least partly formed of a first slope (41), the first slope (10, 41) comprising a set of most recent noise-reduced samples of the second noise reduction frame, not summed with the samples of any other second noise reduction frame. The method reduces the delay caused by speech coding and noise reduction.

Data supplied from the *esp@cenet* database - Worldwide